

Premier Elite communicators provide reliable, flexible and interchangeable signaling options. A variety of protocols, interface formats and multi-path transmission routes guarantees a communication solution to suit any installation requirement. Premier Elite communicators are used with Premier Elite control panels, with some models also compatible with Premier Series control panels.



## Premier Elite ComWiFi

WiFi connectivity provides a host of benefits to Premier Elite systems, including compatibility with Texecom's suite of Premier Elite Mobile Apps, and upload/download diagnostic control via Wintex software.




## Premier Elite ComIP

Allows connection from the Premier Elite Series control panels to a Local or Wide Area Network (LAN/WAN). This allows alarms to be signalled over an IP network to an alarm receiving centre via Texecom's Montex Software. Enables full upload/download & system programming. Compatible with Texecom's suite of Premier Elite Mobile Apps.


## Premier Elite Com300

Plug-on multi-protocol digital communicator/300-baud modem. Enables full upload/download & system programming.



## Premier Elite Com2400

Plug-on multi-protocol digital communicator/2400-baud modem enabling SMS text messaging. Enables full upload/download & system programming.



## Premier Elite ComGSM

GPRS alarm reporting and upload/download:

- Fixed or dynamic SIM card compatible
- Program panel communicator as 'Com IP'
- Requires Premier Montex and Wintex software

GSM text messaging for reporting system events and remote arm/disarm:

- Can be used with 'Pay as you go' SIM cards
- Program panel communicator as 'GSM Module'



Texecom products are designed and manufactured in the UK

[www.texe.com](http://www.texe.com)  
Sales: +44 (0)1706 220460

## Com300 Specifications



Electrical	
Supply Voltage	9 to 13.7VDC
Current Consumption	25mA quiescent; 80mA when active
Environmental	
Operating Temperature	-10°C to +55°C
Maximum Humidity	95% non-condensing
Physical	
Dimensions	95mm x 65mm x 25mm
Packed Weight	50g approx.

## ComWiFi Specifications



Electrical	
Supply Voltage	10 to 14VDC
Current Consumption	210mA
Environmental	
Operating Temperature	-10°C to +55°C
Maximum Humidity	95% non-condensing
Physical	
Dimensions	63mm x 55mm x 15mm
Packed Weight	60g approx.

## Com2400 Specifications



Electrical	
Supply Voltage	9 to 13.7VDC
Current Consumption	25mA quiescent; 80mA when active
Environmental	
Operating Temperature	-10°C to +55°C
Maximum Humidity	95% non-condensing
Physical	
Dimensions	95mm x 65mm x 25mm
Packed Weight	50g approx.

## ComIP Specifications



Electrical	
Supply Voltage	10 to 14VDC
Current Consumption	210mA
Environmental	
Operating Temperature	-10°C to +55°C
Maximum Humidity	95% non-condensing
Physical	
Dimensions	63mm x 55mm x 15mm
Packed Weight	60g approx.

## ComGSM Specifications



Electrical	
Supply Voltage	9 to 14VDC
Current Consumption	35mA quiescent; 100mA when active
Environmental	
Operating Temperature	-10°C to +55°C
Maximum Humidity	95% non-condensing
Physical	
Dimensions	145mm x 90mm x 30mm
Packed Weight	200g approx.

## Features & Functions

Premier Elite Communicators	Com300	Com2400	ComGSM	ComIP	ComWiFi
Premier Elite Series Compatible	•	•	•	•	•
Modem Speed (Baud)	300	2400	9600	19200	N/A
SMS Text Facility		•	•		
Push Notification Compatible			•	•	•
ATS Class	2	2	4	4	2
Upload/Download	•	•	GPRS only	•	•
EN 50131-1	Grade3	Grade3	Grade3	Grade3	Grade2
EN 50136-2-3	Grade2	Grade2	Grade3	Grade3	N/A



Texecom products are designed and manufactured in the UK

www.texe.com  
Sales: +44 (0)1706 220460