

LBB 1956/00 Plena Voice Alarm Call station



Security Systems



- Stylish 6-zone call station, intended for LBB 1990/00 Voice Alarm System Controller
- Six zone selection keys, all-call key and momentary PTT-key for calls
- Selectable gain, speech filter and limiter for improved intelligibility
- LED indications for zone selection, fault and emergency state
- Call station extension provides 7 additional zone and zone group keys

The Plena 6-zone call station is a stylish high quality call station with a stable metal base design, a flexible microphone stem and a unidirectional condenser microphone. It is intended for making calls to selected zones (1 to 6 and all-call) in a PA system built around the LBB1990/00 Voice Alarm System. Except for table-top use, the special design allows also for neatly flush mounting in desk tops. The Plena Voice Alarm Keypad (LBB 1957/00) is an extension adding 7 additional function keys

Functions

On each call station it is possible to select 6 zones with the possibility to connect up to 8 call station keypads (LBB 1957/00) to increase the number of zones or zone groups that can be selected. Each keypad adds 7 zone or zone group keys. This call station features selectable gain, a selectable speech filter and a limiter for improved intelligibility, even if the speaker moves in front of the microphone. Because the call station provides a balanced line level output, it can be positioned up to 1000 m away from the controller, using CAT-5 extension cables.

Using dipswitches on the bottom of the call station different microphone gain levels can be selected as well as the call station ID and the speech filter. Selected zones are indicated with LEDs on the call station, three additional LEDs give visible feedback on the active state of the microphone and the system. Green indicates microphone active, amber indicates that the system has detected a fault (IEC 80649) and red indicates that the system is in the emergency state.

Parts included

Qty Components

- 1 LBB 1956/00 Plena Voice Alarm Call Station or
LBB 1957/00 Plena Voice Alarm Keypad
- 1 Cable terminated with a lockable CAT-5 connector

Certifications and Approvals

EMC emission	acc. to EN 55103-1
EMC immunity	acc. to EN 55103-2

Technical Specifications

LBB 1956/00 Plena Voice Alarm Call station	
ELECTRICAL	
Power supply	
Voltage range	18 – 24V 24 V by LBB 1990/00 or external power supply
Current consumption	<30 mA Call Station <15 mA Key Pad
Performance	
Nominal sensitivity	85 dB SPL (gain preset 0dB)
Nominal output level	700 mV
Maximum input sound level	110 dB SPL
Gain preset	+6 / 0 / -15 dB
Limiter threshold	2 V
Compression ratio limiter	20:1
Distortion	<0.6% (maximum input)
Equivalent input noise level	25 dB SPLA
Frequency response	100Hz – 16kHz
Speech filter	-3 dB @ 315 Hz, high-pass, 6 dB/oct
Output impedance	200 Ohms
Selections	
ENVIRONMENTAL	
Operating temperature range	-10°C to +55°C
Storage temperature range	-40°C to +70°C
Relative humidity	<95%
MECHANICAL	
base	40x100x235 mm (1.57x3.97x9.25 in)
stem length with microphone	390 mm (15.35 in)
Cable length	5 m (196.85 in)
Weight approx.	1 kg
Ordering Information	
LBB 1956/00 Plena Voice Alarm Call station	LBB195600
Hardware Accessories	
LBB 1957/00 Plena Voice Alarm Keypad	LBB195700

Bosch Security Systems

For more information please visit
www.boschsecuritysystems.com

