

CCTV PRODUCTS & IP SOLUTIONS PORTFOLIOS



2013 Version 2

DAHUA TECHNOLOGY

MAKE YOUR LIFE SAFER

NVR

Super NVR

NVR6000/6000D/6000DR

128CH 3U Super NVR



- Up to 128ch IP camera inputs
- 1/1ch Mic in/out, 1ch audio out
- 64ch@1080p, 128ch@720p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- 6 HDMI sync output/1 VGA & 5 HDMI sync output
- 16/8ch alarm in/out, Hot-Swap HDD, RAID 0/1/5
- 16ch sync realtime playback
- 16 SATA, 1 eSATA, 4 USB, 4 RJ45(1000M)
- * -D: LCD screen; -DR: LCD screen, Redundant power
- * Default: 2 HDMI+1VGA

NVR6064/6064D/6064DR

64CH 3U Super NVR



- Up to 64ch IP camera inputs
- 1/1ch Mic in/out, 1ch audio out
- 32ch@1080p, 64ch@720p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- 6 HDMI sync output/1 VGA & 5 HDMI sync output
- 16/8ch alarm in/out, Hot-Swap HDD, RAID 0/1/5
- 16ch sync realtime playback
- 16 SATA, 1 eSATA, 4 USB, 4 RJ45(1000M)
- * -D: LCD screen; -DR: LCD screen, Redundant power
- * Default: 2 HDMI+1VGA

Professional NVR

NVR5032

32CH 3U NVR



- 32ch IP camera inputs
- 1/1ch Mic in/out
- 16ch@1080p, 32ch@720p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- HDMI, VGA output up to 1080p, 1 TV
- 16ch alarm in & 6ch relay out, RS485, RS232
- 16 SATA, 1 eSATA, 4 USB, 2 RJ45(1000M)
- Incoming bandwidth: 160Mbps

NVR5808/5816/5832

8/16/32CH 2U NVR



- 8/16/32ch IP camera inputs
- 1/1ch Mic in/out
- 8/16/32ch@1080p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- HDMI, VGA output up to 1080p, 1 TV
- 8/16/16ch alarm in & 3/6/6ch relay out, RS485, RS232
- 8 SATA, 1 eSATA, 4 USB, 2 RJ45(1000M)
- Incoming bandwidth: 160Mbps

NVR5808/5816/5832-8P

8/16/32CH 8-PoE 2U NVR



- 8/16/32ch IP camera inputs
- 1/1ch Mic in/out
- 8/16/32ch@1080p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- HDMI, VGA output up to 1080p, 1 TV
- 8/16/16ch alarm in & 3/6/6ch relay out, RS485, RS232
- 8 SATA, 1 eSATA, 4 USB, 2 RJ45(1000M)
- Incoming bandwidth: 160Mbps
- 8 PoE ports

NVR5408/5416/5432

8/16/32CH 1.5U NVR



- 8/16/32ch IP camera inputs
- 1/1ch Mic in/out
- 8/16/32ch@1080p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- HDMI, VGA output up to 1080p, 1 TV
- 8/16/16ch alarm in & 3/6/6ch relay out, RS485, RS232
- 4 SATA, 1 eSATA, 3 USB, 1 RJ45(1000M)
- Incoming bandwidth: 160Mbps

NVR5408/5416/5432-8P

8/16/32CH 8-PoE 1.5U NVR



- 8/16/32ch IP camera inputs
- 1/1ch Mic in/out
- 8/16/32ch@1080p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- HDMI, VGA output up to 1080p, 1 TV
- 8/16/16ch alarm in & 3/6/6ch relay out, RS485, RS232
- 4 SATA, 1 eSATA, 3 USB, 1 RJ45(1000M)
- Incoming bandwidth: 160Mbps
- 8 PoE ports

NVR5416/5432-16P

16/32CH 16-PoE 1.5U NVR



- 8/16/32ch IP camera inputs
- 1/1ch Mic in/out
- 16/32ch@1080p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- HDMI, VGA output up to 1080p, 1 TV
- 16ch alarm in & 6ch relay out, RS485, RS232
- 4 SATA, 1 eSATA, 3 USB, 1 RJ45(1000M)
- Incoming bandwidth: 160Mbps
- 16 PoE ports

NVR5208/5216/5232

8/16/32CH 1U NVR



- 8/16/32ch IP camera inputs
- 1/1ch Mic in/out
- 8/16/32ch@1080p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- HDMI, VGA output up to 1080p, 1 TV
- 8ch alarm in & 3ch relay out, RS485, RS232
- 2 SATA, 2 USB, 1 RJ45(1000M)
- Incoming bandwidth: 160Mbps

Professional Lite NVR

NVR5208/5216/5232-8P

8/16/32CH 8-PoE 1U NVR



- 8/16/32ch IP camera inputs
- 1/1ch Mic in/out
- 8/16/32ch@1080p
- Compatible with 5Mp, 3Mp, 1080p, 720p, D1 and etc.
- HDMI, VGA output up to 1080p, 1 TV
- 8ch alarm in & 3ch relay out, RS485, RS232
- 2 SATA, 2 USB, 1 RJ45(1000M)
- Incoming bandwidth: 160Mbps
- 8 PoE Ports

NVR3804/3808/3816

4/8/16CH 2U NVR



- 4/8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p, 1 TV
- 4/8/16ch alarm in & 6ch relay out, RS485, RS232
- 8 SATA, 1 eSATA, 4 USB, 1 RJ45(1000M)

NVR3404/3408/3416V

4/8/16CH 4HDD Vertical NVR



- 4/8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p
- 3ch alarm in & 1ch relay out, RS485
- 4 SATA, 1eSATA, 3 USB, 1 RJ45(1000M)

NVR3404/3408/3416V-P

4/8/16CH 4HDD 4-PoE Vertical NVR



- 4/8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p
- 3ch alarm in & 1ch relay out, RS485
- 4 SATA, 1eSATA, 3 USB, 1 RJ45(1000M)
- 4 PoE ports

NVR3204/3208/3216V

4/8/16CH 2HDD Vertical NVR



- 4/8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p
- 3ch alarm in & 1ch relay out, RS485
- 2 SATA, 1eSATA, 3 USB, 1 RJ45(1000M)

NVR3204/3208/3216V-P

4/8/16CH 2HDD 4-PoE Vertical NVR



- 4/8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p
- 3ch alarm in & 1ch relay out, RS485
- 2 SATA, 1eSATA, 3 USB, 1 RJ45(1000M)
- 4 PoE ports

NVR3204/3208/3216

4/8/16CH 1U NVR



- 4/8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p, 1 TV
- 4/8/16ch alarm in & 3ch relay out, RS485, RS232
- 2 SATA, 2 USB, 1 RJ45(1000M)

NVR3204/3208/3216-P

4/8/16CH 4-PoE 1U NVR



- 4/8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p, 1 TV
- 4/8/16ch alarm in & 3ch relay out, RS485, RS232
- 2 SATA, 2 USB, 1 RJ45(1000M)
- 4 PoE ports

NVR3208/3216-8P

8/16CH 8-PoE 1U NVR



- 8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p, 1 TV
- 8/16ch alarm in & 3ch relay out, RS485, RS232
- 2 SATA, 2 USB, 1 RJ45(1000M)
- 8 PoE ports

NVR3104/3108/3116H

4/8/16CH Mini 1U NVR



- 4/8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p
- 2ch alarm in & 1ch relay out
- 1 SATA, 2 USB, 1 RJ45 (100M)

NVR3104/3108/3116H-P

4/8/16CH 4-PoE Mini 1U NVR



- 4/8/16ch IP camera inputs
- 1/1ch Mic in/out
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p
- 2ch alarm in & 1ch relay out
- 1 SATA, 2 USB, 1 RJ45 (100M)
- 4 PoE ports

NVR3104/3108/3116

4/8/16CH Smart 1U NVR



- 4/8/16ch IP camera inputs
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p
- 1 SATA, 2 USB, 1 RJ45 (100M)

Entry-Level NVR

NVR3104/3108/3116-P

4/8/16CH 4-PoE Smart 1U NVR



- 4/8/16ch IP camera inputs
- Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p
- 1 SATA, 2 USB, 1 RJ45 (100M)
- 4 PoE ports

NVR2104/2108H

4/8CH Mini 1U NVR



- 4/8ch IP camera inputs
- 1/1ch Mic in/out
- Max 60fps@1080p, 120fps@720p, 240fps@D1
- HDMI, VGA output up to 1080p
- 2ch alarm in & 1ch relay out
- 1 SATA, 2 USB, 1 RJ45 (100M)

NVR2104/2108H-P

4/8CH 4-PoE Mini 1U NVR



- 4/8ch IP camera inputs
- 1/1ch Mic in/out
- Max 60fps@1080p, 120fps@720p, 240fps@D1
- HDMI, VGA output up to 1080p
- 2ch alarm in & 1ch relay out
- 1 SATA, 2 USB, 1 RJ45 (100M)
- 4 PoE ports

NVR

NVR2104/2108

4/8CH Smart Mini 1U NVR



- 4/8ch IP camera inputs
- Max 60fps@1080p, 120fps@720p, 240fps@D1
- HDMI, VGA output up to 1080p
- 1 SATA, 2 USB, 1 RJ45(100M)

NVR2104/2108-P

4/8CH 4-PoE Smart Mini 1U NVR



- 4/8ch IP camera inputs
- Max 60fps@1080p, 120fps@720p, 240fps@D1
- HDMI, VGA output up to 1080p
- 1 SATA, 2 USB, 1 RJ45(100M)
- 4 PoE ports

Mobile NVR

NVR0404MF

4CH PoE Mobile NVR



- 4ch video inputs
- All channel 1080p realtime recording
- 1 VGA output up to SXGA, 2TV
- 8/3ch alarm in/out, RS485
- Car No., GPS, Speed live-view & recording
- GPS / Wi-Fi / 3G optional, 1 RJ45(1000M)
- 2 SATA(Vibration-proof), 1 eSATA, 2 USB

Forensic NVR

NVR0404FD-S

4CH Forensic NVR



- 4ch video inputs
- All channel 1080p realtime recording
- HDMI, VGA output up to 1080p, 1 TV
- 4/2ch alarm in/out, RS485
- 4 SATA(Vibration-proof), 1 eSATA, 2 USB, 2 RJ45(1000M)
- Built-in 7-inch LCD

IPC Support List:



DVR

HD-SDI Hybrid DVR

DVR0404HD-U

8CH HD-SDI & IP 1080P 2U Hybrid DVR



- 4ch HD-SDI video & 4ch IP camera inputs
- 4/1ch audio in/out, 1/1ch Mic in/out
- HD-SDI: 4ch@1080p
- IPC: 4ch@1080p/720p/D1
- HDMI, VGA output up to 1080p, 1 TV
- 4ch alarm in & 6ch relay out
- 4ch sync realtime playback
- 8 SATA, 1 eSATA, 4 USB, 1 RJ45(1000M)

960H Hybrid DVR

DVR0404/0804/1604HF-U-E

8/16/32CH 960H & IP 2U Hybrid DVR



- 4/8/16ch 960H video & 4/8/16ch IP camera inputs
- 4/8/16ch audio in & 1ch audio out, 1/1ch Mic in/out
- 960H : 4/8/16ch@960H
- IPC: Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot, 16 Loop
- 4/8/16ch alarm in & 6ch relay out, RS485
- 16ch sync realtime playback
- 8 SATA, 1 eSATA, 4 USB, 2 RJ45(1000M)

DVR0404/0804/1604HF-UH-E

8/16/32CH 960H & IP 2U Hybrid DVR with Removable HDDs



- 4/8/16ch 960H video & 4/8/16ch IP camera inputs
- 4/8/16ch audio in & 1ch audio out, 1/1ch Mic in/out
- 960H : 4/8/16ch@960H
- IPC: Max 120fps@1080p, 240fps@720p, 480fps@D1
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot, 16 Loop
- 4/8/16ch alarm in & 6ch relay out, RS485
- 16ch sync realtime playback
- 8 SATA(Removable), 1 eSATA, 4 USB, 2 RJ45(1000M)

HD-SDI DVR

DVR0404/0804/1604HD-S

4/8/16CH HD-SDI 1080P 2U DVR



- 4/8/16ch HD-SDI video inputs
- 4/8/16ch audio in & 1ch audio out, 1/1ch Mic in/out
- DVR0404HD-S: Max 100/120fps@1080p
- DVR0804/1604HD-S: Max 200/240fps@1080p
- HDMI, VGA output up to 1080p, 1TV
- 4/8/16ch alarm in & 6ch relay out, RS485
- 4ch sync realtime playback
- 8 SATA, 1 eSATA, 4 USB, 1 RJ45(1000M)

DVR0404/0804/1604HD-L

4/8/16CH HD-SDI 1080P 1.5U DVR



- 4/8/16ch HD-SDI video inputs
- 4/8/16ch audio in & 1ch audio out, 1/1ch Mic in/out
- DVR0404HD-L: Max 100/120fps@1080p
- DVR0804/1604HD-L: Max 200/240fps@1080p
- HDMI, VGA output up to 1080p, 1TV
- 4/8/16ch alarm in & 6ch relay out, RS485
- 4ch sync realtime playback
- 4 SATA, 1 eSATA, 3 USB, 1 RJ45(1000M)

DVR0404HD-A

4CH HD-SDI 1080P 1U DVR



- 4ch HD-SDI video inputs
- 4ch audio in & 1ch audio out, 1/1ch Mic in/out
- Max 100/120fps@1080p
- HDMI, VGA output up to 1080p, 1TV
- 4ch alarm in & 3ch relay out, RS485
- 4ch sync realtime playback
- 2 SATA, 1 eSATA, 2 USB, 1 RJ45(1000M)

Premium DVR

DVR6404LF-S

64CH 2CIF 3U DVR



- 64ch video inputs
- 16/1ch audio in/out, 1/1ch Mic in/out
- All channel@2CIF or every 8ch: 1ch@D1 & 7ch@CIF
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot
- 16/6ch alarm in/out, RS485
- 16ch sync realtime playback
- 8 SATA, 1 eSATA, 4 USB, 1 RJ45(1000M)

DVR2404/3204HF-S

24/32CH D1 2U DVR



- 24/32ch video inputs
- 16/1ch audio in/out, 1/1ch Mic in/out
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot
- 16/6ch alarm in/out, RS485
- 16ch sync realtime playback
- 8 SATA, 1 eSATA, 4 USB, 1 RJ45(1000M)

DVR2404/3204LF-S

24/32CH 2CIF 2U DVR



- 24/32ch video inputs
- 16/1ch audio in/out, 1/1ch Mic in/out
- All channel@2CIF or every 4ch: 1ch@D1 & 3ch@CIF
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot
- 16/6ch alarm in/out, RS485
- 16ch sync realtime playback
- 8 SATA, 1 eSATA, 4 USB, 1 RJ45(1000M)

DVR2404/3204HF-AL

24/32CH D1 1.5U DVR



- 24/32ch video inputs
- 4/1ch audio in/out, 1/1ch Mic in/out
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot
- 16/3ch alarm in/out, RS485
- 16ch sync realtime playback
- 2 SATA, 2 USB, 1 RJ45(1000M)

DVR2404/3204LF-AL

24/32CH 2CIF 1.5U DVR



- 24/32ch video inputs
- 4/1ch audio in/out
- All channel 2CIF or every 4ch: 1ch@D1 & 3ch@CIF
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot
- 16/3ch alarm in/out, RS485
- 16ch sync realtime playback
- 2 SATA, 2 USB, 1 RJ45(1000M)

DVR3224/3232L

24/32CH CIF 1.5U DVR



- 24/32ch video inputs
- 4/1ch audio in/out, 1/1ch Mic in/out
- All channel@CIF realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot
- 16/3ch alarm in/out, RS485
- 16ch sync realtime playback
- 2 SATA, 2 USB, 1 RJ45(1000M)

Professional DVR

DVR0404/0804/1604HF-S-E

4/8/16CH 960H 2U DVR



- 4/8/16ch Effio 960H video inputs
- 4/8/16ch audio in & 1ch audio out, 1/1ch Mic in/out
- All channel@960H(960x576/960x480) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot, 16 Loop
- 4/8/16ch alarm in & 6ch relay out, RS485
- 8 SATA, 1 eSATA, 4 USB, 2 RJ45(1000M)

DVR0404/0804/1604HF-L-E

4/8/16CH 4HDD 960H 1.5U DVR



- 4/8/16ch Effio 960H video inputs
- 4/1ch audio in & out, 1/1ch Mic in/out
- All channel@960H(960x576/960x480) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot, 16 Loop
- 4/8/16ch alarm in & 6ch relay out, RS485
- 4 SATA, 1 eSATA, 2 USB, 1 RJ45(1000M)

DVR0404/0804/1604HF-AL-E

4/8/16CH 2HDD 960H 1.5U DVR



- 4/8/16ch Effio 960H video inputs
- 4/8/4ch audio in & 1ch audio out, 1/1ch Mic in/out
- All channel@960H(960x576/960x480) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot
- 4/8/16ch alarm in & 3ch relay out, RS485
- 2 SATA, 2 USB, 1 RJ45(1000M)

Professional Lite DVR

DVR0404/0804/1604HF-A-E

4/8/16CH 960H 1U DVR



- 4/8/16ch Effio 960H video inputs
- 4/8/4ch audio in & 1ch audio out, 1/1ch Mic in/out
- All channel@960H(960x576/960x480) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot
- 4/8/16ch alarm in & 3ch relay out, RS485
- 2 SATA, 2 USB, 1 RJ45(1000M)

DVR5804/5808/5816

4/8/16CH D1 2U DVR



- 4/8/16ch video inputs
- 4/8/16ch audio in & 1ch audio out
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 spot
- 4/8/16ch alarm in & 3ch relay out, RS485
- 4/8/16ch sync realtime playback
- 8 SATA, 1eSATA, 4USB, 1 RJ45(1000M)

DVR5404/5408/5416

4/8/16CH D1 1.5U DVR



- 4/8/16ch video inputs
- 4/1ch audio in/out
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 spot
- 4/8/16ch alarm in & 3ch relay out, RS485
- 4/8/16ch sync realtime playback
- 4 SATA, 1eSATA, 2 USB, 1 RJ45(1000M)

DVR

DVR5204L/5208L/5216L

4/8/16CH D1 1.5U DVR



- 4/8/16ch video inputs
- 4/1ch audio in/out
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 spot
- 4/8/16ch alarm in & 3ch relay out, RS485
- 4/8/16ch sync realtime playback
- 2 SATA, 2 USB, 1 RJ45(100M)

DVR5204A/5208A/5216A

4/8/16CH D1 1U DVR



- 4/8/16ch video inputs
- 4/1ch audio in/out
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 spot
- 4/8/16ch alarm in & 3ch relay out, RS485
- 4/8/16ch sync realtime playback
- 2 SATA, 2 USB, 1 RJ45(100M)

DVR1604LF-AL

16CH 2CIF 1.5U DVR



- 16ch video inputs
- 4/1ch audio in/out
- All channel@2CIF realtime recording
- HDMI, VGA output up to 1080p, 1 TV, 1 Spot
- 16ch alarm in & 3ch out, RS485
- 16ch sync realtime playback
- 2 SATA, 2 USB, 1 RJ45(100M)

Entry-Level DVR

DVR5104/5108/5116HE

4/8/16CH D1 Mini 1U DVR



- 4/8/16ch video inputs
- 4/1ch audio in/out
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV
- 4/8/16ch alarm in & 3/3/1ch relay out
- 4/8/16ch sync realtime playback
- 1 SATA, 2 USB, RS485, 1 RJ45(100M)

DVR5104/5108/5116H

4/8/16CH D1 Mini 1U DVR



- 4/8/16ch video inputs
- 1/1ch audio in/out
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV
- 4/8/16ch sync realtime playback
- 1 SATA, 2 USB, RS485, 1 RJ45(100M)

DVR5104/5108C

4/8CH D1 Smart Mini 1U DVR



- 4/8ch video inputs
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV
- 4/8ch sync realtime playback
- 1 SATA, 2 USB, 1 RJ45(100M)

DVR5116C

16CH D1 Smart Mini 1U DVR



- 16ch video inputs
- All channel@D1(4CIF) realtime recording
- HDMI, VGA output up to 1080p, 1 TV
- 16ch sync realtime playback
- 1 SATA, 2 USB, 1 RJ45(100M)

DVR2104/2108/2116HE

4/8/16CH 2CIF Mini 1U DVR



- 4/8/16ch video inputs
- 4/1ch audio in/out
- All channel@2CIF realtime recording
- HDMI, VGA output up to 1080p, 1 TV
- 4/8/16ch alarm in & 3/3/1ch relay out
- 4/8/16ch sync realtime playback
- 1 SATA, 2 USB, RS485, 1 RJ45(100M)

DVR2104/2108/2116H

4/8/16CH 2CIF Mini 1U DVR



- 4/8/16ch video inputs
- 1/1ch audio in/out
- All channel@2CIF realtime recording
- HDMI, VGA output up to 1080p, 1 TV
- 4/8/16ch sync realtime playback
- 1 SATA, 2 USB, RS485, 1 RJ45(100M)

Combo DVR

DVR2104/2108C

4/8CH 2CIF Smart Mini 1U DVR



- 4/8ch video inputs
- All channel@2CIF realtime recording
- HDMI, VGA output up to 1080p
- 4/8ch sync realtime playback
- 1 SATA, 2 USB, 1 RJ45(100M)

DVR2116C

16CH 2CIF Smart Mini 1U DVR



- 16ch video inputs
- All channel@2CIF realtime recording
- HDMI, VGA output up to 1080p, 1 TV
- 16ch sync realtime playback
- 1 SATA, 2 USB, 1 RJ45(100M)

CVR0404/0804-10(T)

4/8CH 10" LCD Combo DVR



- 4/8ch video inputs
- 4/1ch audio in/out, 1ch Mic out
- CVR0404-10(T): 1ch D1 & 3ch CIF realtime recording
- CVR0804-10(T): All channel CIF realtime recording
- 4/1ch alarm in/out, RS485, 1 TV
- 1 SATA, 2 USB, RJ45(100M)
- 10" LCD(800x600)
- * CVR0404/0804-10T: Touch Screen

Mobile DVR

DVR0404/0604MF-H/0804MF-U

4/6/8CH Mobile DVR



- 4/6/8ch video inputs
- 4/6/8ch audio in & 1ch audio out, 1/1ch Mic in/out
- DVR0404/0604MF-H: All channel D1(4CIF)
- DVR0804MF-U: 2ch@D1+6ch@CIF
- 1 VGA output up to SXGA, 2TV
- 7/2ch alarm in/out, RS485
- Car No., GPS, Speed live-view & recording
- GPS / Wi-Fi / 3G optional, 1 RJ45(100M)
- 2 SATA(Vibration-proof), 1 eSATA, 2 USB

DH-DVR0404ME-HE

4CH Mobile DVR



- 4ch video inputs
- 4/1ch audio in/out, 1/1ch Mic in/out
- Full channel@960H realtime recording
- 1 VGA output up to SXGA, 2TV
- 7/2ch alarm in/out, RS485
- Car No., GPS, Speed live-view & recording
- GPS / Wi-Fi / 3G optional, 1 RJ45(100M)
- SSD/Heater optional, CAN support
- 1 SATA(Vibration-proof), 2 USB

DVR0404ME-H/0404ME-U

4CH Mobile DVR



- 4ch video inputs
- 4/1ch audio in/out, 1/1ch Mic in/out
- DVR0404ME-H: All channel@D1(4CIF)
- DVR0404ME-U: 1ch@D1+3ch@CIF
- 1 VGA output up to SXGA, 2TV
- 7/2ch alarm in/out, RS485
- Car No., GPS, Speed live-view & recording
- GPS / Wi-Fi / 3G optional, 1 RJ45(100M)
- 1 SATA(Vibration-proof), 2 USB

ATM DVR

DH-DVR0404ME-SU

4CH Mobile DVR



- 4ch video inputs
- 4/1ch audio in/out, 1/1ch Mic in/out
- Full channel@CIF realtime recording
- 1 VGA output up to SXGA, 2TV
- 7/2ch alarm in/out, RS485
- Car No., GPS, Speed live-view & recording
- GPS/3G optional, 1 RJ45(100M)
- 2 SD cards, 2 USB

DVR0404AH-U/0404AL-U(UD)

4CH D1 ATM DVR



- 4ch video inputs
- 4/1ch audio in/out, 1/1ch Mic in/out
- DVR0404AH-U(UD): All channel@D1(4CIF)
- DVR0404AL-U(UD): 1ch@D1+3ch@CIF
- VGA output up to SXGA, 1 TV
- 6/3ch alarm in/out, RS485
- ATM/POS info live-view, recording & playback
- 4 SATA, 1 eSATA, 2 USB, 1 RJ45(100M)
- *UD: with screen

DVR0404AS-U(UD)

4CH ATM DVR



- 4ch video inputs
- 4/1ch audio in/out, 1/1ch Mic in/out
- 1ch D1 & 3ch CIF realtime recording
- VGA output up to SXGA, 1 TV
- 6/2ch alarm in/out, RS485
- ATM/POS info live-view, recording & playback
- 2 SATA, 2 USB, 1 RJ45(100M)
- *UD: with screen

Network Camera

5 Megapixel Series

IPC-HF3500

5Megapixel Full-HD Network Camera



- 1/2.5" 5 Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 8fps@5M(2560x1920), 15fps@3M(2048x1536), 25/30fps@1080P
- D&N(ICR), Auto Iris, SD card
- Wi-Fi(optional), DC12V/AC24V, PoE
- Material: Metal

3 Megapixel WDR Series

IPC-HF3301

3Megapixel Full-HD WDR Network Camera



- 1/3" 3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@3M(2048x1536), 25/30fps@1080p
- WDR,3DNR,D&N(ICR), Auto Iris, Micro SD card
- DC12V, PoE
- Material: Metal

IPC-HFW3301C

3Megapixel Full-HD WDR Network IR-Bullet Camera



- 1/3" 3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@3M(2048x1536), 25/30fps@1080p
- Lens: 3 ~12mm/F1.4, IR LEDs: 20m
- WDR,3DNR,D&N(ICR), Auto Iris, Micro SD card
- IP66, DC12V(AC24 optional), PoE
- Material: Plastic(upper cover)+Metal(the rest)

IPC-HDB3301

3Megapixel Full-HD WDR Vandal-proof Network Dome Camera



- 1/3" 3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@3M(2048x1536), 25/30fps@1080p
- Lens: 3.3 ~12mm/F1.4
- WDR, 3DNR, D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, DC12V/AC24V, PoE
- Material: Metal

IPC-HDBW3301

3Megapixel Full-HD WDR Vandal-proof Network IR Dome Camera



- 1/3" 3 Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@3M(2048x1536), 25/30fps@1080p
- Lens: 3.3 ~12mm/F1.4, IR LEDs:20m
- WDR, 3DNR, D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, DC12V/AC24V, PoE
- Material: Metal

IPC-HDB3301-DI

3Megapixel Full-HD WDR Vandal-proof Network In-ceiling Dome Camera



- 1/3" 3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@3M(2048x1536), 25/30fps@1080p
- Lens: 3.3 ~12mm/F1.4
- WDR, 3DNR, D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

Network Camera

3Megapixel Series

IPC-HDBW3301-DI

3Megapixel Full-HD WDR Vandal-proof Network IR In-ceiling Dome Camera



- 1/3" 3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@3M(2048x1536), 25/30fps@1080p
- Lens: 3.3~12mm/F1.4, IR LEDs: 20m
- WDR, 3DNR, D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

IPC-HF3300

3Megapixel Full-HD Network Camera



- 1/2.8" 3Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 20fps@3M(2048x1536), 25/30fps@1080p
- D&N(ICR), Auto Iris, SD card
- Wi-Fi(optional), AC24V/DC12V, PoE
- Material: Metal

IPC-HFW3300

3Megapixel Full-HD Network IR Camera



- 1/2.8" 3Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 20fps@3M(2048x1536), 25/30fps@1080p
- Lens: 8~16mm/F1.6, IR LEDs: 30m
- D&N(ICR), Auto Iris, Micro SD card
- IP66, DC12V(AC24 optional), PoE
- Material: Metal

IPC-HFW3300C

3Megapixel Full-HD Network IR-Bullet Camera



- 1/2.8" 3Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 20fps@3M(2048x1536), 25/30fps@1080p
- Lens: 3.3~12mm/F1.4, IR LEDs: 20m
- D&N(ICR), Auto Iris, Micro SD card
- IP66, DC12V(AC24 optional), PoE
- Material: Plastic (upper cover)+ Metal (the rest)

IPC-HDB3300

3Megapixel Full-HD Vandal-proof Network Dome Camera



- 1/2.8" 3Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 20fps@3M(2048x1536), 25/30fps@1080p
- Lens: 3.3~12mm/F1.4
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

IPC-HDBW3300

3Megapixel Full-HD Vandal-proof Network IR Dome Camera



- 1/2.8" 3Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 20fps@3M(2048x1536), 25/30fps@1080p
- Lens: 3.3~12mm/F1.4, IR LEDs: 20m
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

2 Megapixel Series

IPC-HF3200

2Megapixel Full-HD Network Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- D&N(ICR), Auto Iris, SD card
- Wi-Fi(optional), AC24V/DC12V, PoE
- Material: Metal

IPC-HFW3200/3202C

2Megapixel Full-HD (Motorized) Network IR-Bullet Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.3~12mm/F1.4 (3200C)
- Motorized Lens: 3~9mm/F1.2 (3202C)
- D&N(ICR), Auto Iris, Micro SD card, IR LEDs: 20m
- IP66, DC12V(AC24 optional), PoE
- Material: Plastic (upper cover)+ Metal (the rest)

IPC-HFW3200S

2Megapixel Full-HD Network Small IR-Bullet Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 6mm(3.6mm, 8mm optional)
- D&N(ICR), IR LEDs: 20m
- IP66, DC12V, PoE
- Material: Plastic (upper cover)+ Metal (the rest)

IPC-HDB3200/3202

2Megapixel Full-HD Vandal-proof (Motorized) Network Dome Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.3~12mm/F1.4 (3200)
- Motorized Lens: 3~9mm/F1.2 (3202)
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

IPC-HDBW3200/3202

2Megapixel Full-HD Vandal-proof (Motorized) Network IR Dome Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.3~12mm/F1.4 (3200)
- Motorized Lens: 3~9mm/F1.2 (3202)
- IR LEDs: 20m
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

IPC-HDB3200/3202-DI

2Megapixel Full-HD Vandal-proof (Motorized) Network In-ceiling Dome Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.3~12mm/F1.4 (3200)
- Motorized Lens: 3~9mm/F1.2 (3202)
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

IPC-HDBW3200/3202-DI

2Megapixel Full-HD Vandal-proof (Motorized) Network IR In-ceiling Dome Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.3~12mm/F1.4 (3200)
- Motorized Lens: 3~9mm/F1.2 (3202), IR LEDs: 20m
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

IPC-HDB3200C

2Megapixel Full-HD Vandal-proof Network Mini Dome Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.6(2.8mm, 6mm, 8mm optional)
- Micro SD card
- IK10, IP66, DC12V, PoE
- Material: Metal

IPC-HD3200

2Megapixel Full-HD Network Indoor Dome Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.3~12mm/F1.4
- D&N(ICR), Auto Iris, Micro SD card
- DC12V, PoE
- Material: Plastic(outside)

1.3 Megapixel WDR Series

IPC-HDW3200

2Megapixel Full-HD Network Indoor IR Dome Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.3 ~12mm/F1.4, IR LEDs: 20m
- D&N(ICR), Auto Iris, Micro SD card
- DC12V, PoE
- Material: Plastic(outside)

IPC-HDW3200S

2Megapixel Full-HD Network IR Mini Dome Camera



- 1/3" 2Mp Exmor CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1080p
- Lens: 3.6 (6mm optional)
- D&N(ICR), IR LEDs: 20m
- IP66, DC12V, PoE
- Material: Metal(inner core)+plastic(outside)

IPC-HF3101

1.3Megapixel HD WDR Network Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1.3M(1280×960)/720p
- WDR, 3DNR, D&N(ICR), Auto Iris, SD card
- Wi-Fi(optional), AC24V/DC12V, PoE
- Material: Metal

IPC-HFW3101C

1.3Megapixel HD WDR Network IR-Bullet Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1.3M(1280×960)/720p
- Lens: 2.8~12mm/F1.4, IR LEDs: 20m
- WDR, D&N(ICR), Auto Iris, Micro SD card
- IP66, 3DNR, DC12V(AC24V optional), PoE
- Material: Plastic (upper cover)+ Metal (the rest)

IPC-HDB3101

1.3Megapixel HD WDR Vandal-proof Network Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1.3M(1280×960)/720p
- Lens: 2.8~12mm/F1.4
- WDR, 3DNR, D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

IPC-HDBW3101

1.3Megapixel HD WDR Vandal-proof Network IR Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1.3M(1280×960)/720p
- Lens: 2.8~12mm/F1.4, IR LEDs: 20m
- WDR, 3DNR, D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

1.3 Megapixel Series

IPC-HDB3101-DI

1.3Megapixel HD WDR Vandal-proof Network In-ceiling Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1.3M(1280×960)/720p
- Lens: 2.8~12mm/F1.4
- WDR, 3DNR, D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

IPC-HDBW3101-DI

1.3Megapixel HD WDR Vandal-proof Network IR In-ceiling Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1.3M(1280×960)/720p
- Lens: 2.8~12mm/F1.4, IR LEDs: 20m
- WDR, 3DNR, D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, AC24V/DC12V, PoE
- Material: Metal

IPC-HF3100

1.3Megapixel HD Network Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 25/30fps@1.3M(1280×960)/720p
- D&N(ICR), Auto Iris, SD card
- Wi-Fi(optional), AC24V/DC12V, PoE
- Material: Metal

Network Camera

IPC-HDB3100

1.3Megapixel HD Vandal-proof Network Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@1.3M(1280×960), 25/30fps@720p
- Lens: 2.8~12mm/F1.4
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, DC12V, PoE
- Material: Metal

IPC-HDBW3100

1.3Megapixel HD Vandal-proof Network IR Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@1.3M(1280×960), 25/30fps@720p
- Lens: 2.8~12mm/F1.4, IR LEDs:20m
- D&N(ICR), Auto Iris, Micro SD card
- IK10, IP66, DC12V, PoE
- Material: Metal

IPC-HD3100

1.3Megapixel HD Network Indoor Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@1.3M(1280×960), 25/30fps@720p
- Lens: 2.8~12mm/F1.4
- D&N(ICR), Auto Iris, Micro SD card
- DC12V, PoE
- Material: Plastic(outside)

1.3 Megapixel Series

IPC-HDW3100

1.3Megapixel HD Network IR Indoor Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@1.3M(1280×960), 25/30fps@720p
- Lens: 2.8-12mm /F1.4
- D&N(ICR), Auto Iris, Micro SD card, IR LEDs: 20m
- DC12V, PoE
- Material: Plastic(outside)

IPC-HFW2100

1.3Megapixel HD Network Mini IR-Bullet Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@1.3M(1280×960), 25/30fps@720p
- Lens: 6mm(3.6mm, 8mm optional)
- D&N(ICR), IR LEDs: 20m
- IP66, DC12V, PoE
- Material: Metal

IPC-HD2100

1.3Megapixel HD Network Mini Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@1.3M(1280×960), 25/30fps@720p
- Lens: 3.6mm(2.8mm, 6mm, 8mm optional)
- DC12V, PoE
- Material: Plastic

Home-use Series

IPC-HDW2100

1.3Megapixel HD Network IR Mini Dome Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@1.3M(1280×960), 25/30fps@720p
- Lens: 3.6mm(2.8mm, 6mm optional)
- D&N(ICR), IR LEDs: 20m
- IP66, DC12V, PoE
- Material: Metal(inner core)+Plastic(outside)

IPC-K100/100A

1.3Megapixel HD Network Cube Camera



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@1.3M(1280×960),25/30fps@720p
- Lens: 3.6mm
- IPC-K100: White LEDs: 10m
- IPC-K100A: MicroSD card, White LEDs: 10m
- DC12V, PoE
- Material: Plastic(front)+Metal(back)

IPC-K100W

1.3Megapixel HD Network Cube Camera (Wi-Fi Version)



- 1/3" 1.3Mp Aptina CMOS
- H.264/MJPEG & dual-stream encoding
- Max 15fps@1.3M(1280×960),25/30fps@720p
- Lens: 3.6mm
- MicroSD card, White LEDs: 10m
- Wi-Fi, DC12V
- Material: Plastic(front)+Metal(back)

HD Zoom Camera

IPC-K6-I

VGA Network Cube Camera



- 1/4" VGA CMOS
- H.264 & dual-stream encoding
- 25/30fps@VGA/CIF/QVGA
- Lens: 4.3mm/F1.8, IR LEDs: 10m
- D&N(ICR), Micro SD card
- DC5V
- Material: Plastic

IPC-A7-I

VGA Network P/T Camera



- 1/4" VGA CMOS
- H.264 & dual-stream encoding
- 25/30fps@VGA/CIF/QVGA
- Pan/Tilt driver
- Lens: 4.3mm/F1.8, IR LEDs: 10m
- D&N(ICR), SD card
- Wi-Fi(A7W-I), DC5V
- Material: Plastic

SDZ2020B-N

20x 2Mp Full-HD Network Zoom Camera



- 1/3" 2Mp Exmor CMOS
- Max 25/30fps@1080P
- 4.7~94mm 20x optical zoom, Auto focus
- H.264/MJPEG & Dual-stream encoding
- DWDR, D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 2/1ch alarm in/out, RS485
- DC12V(AC24V optional), PoE, Micro SD card

SDZ1018B-N

18x 1.3Mp HD Network Zoom Camera



- 1/3" 1.3Mp CMOS
- Max 25/30fps@1.3M/720p
- 4.7~84.6mm 18x optical zoom, Auto focus
- H.264/MJPEG & Dual-stream encoding
- 120db WDR, D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 2/1ch alarm in/out, RS485
- DC12V(AC24V optional), PoE, Micro SD card

VMS Partners :



HD-SDI Camera

Fixed Camera

HDC-HF3200

2Megapixel Full-HD HD-SDI Camera



- 1/3" 2Mp Exmor CMOS
- 25/30fps@1080p,50/60fps@720p
- D&N(ICR), Auto Iris
- AC24V/DC12V
- Material: Metal

HDC-HFW2200S

2Megapixel Full-HD IR-Bullet HD-SDI Camera



- 1/3" 3Mp CMOS
- 25/30fps@1080p,50/60fps@720p
- Lens: 3.6mm/F1.6 (6mm optional), IR LEDs: 20m
- D&N(ICR)
- IP66, DC12V
- Material: Plastic (upper cover)+ Metal (the rest)

HDC-HDW2200S

2Megapixel Full-HD Vandal-proof HD-SDI IR Dome Camera



- 1/3" 3Mp CMOS
- 25/30fps@1080p,50/60fps@720p
- Lens: 3.6mm/F1.6 (6mm optional), IR LEDs: 20m
- D&N(ICR)
- IP66, DC12V
- Material: Metal(inner core)+plastic(outside)

HDC-HFW3200C

2Megapixel Full-HD IR-Bullet HD-SDI Camera



- 1/3" 2Mp Exmor CMOS
- 25/30fps@1080p,50/60fps@720p
- D&N(ICR), Auto Iris
- Lens: 3.3~12mm/F1.4, IR LEDs: 20m
- IP66, AC24V/DC12V
- Material: Plastic (upper cover)+ Metal (the rest)

HDC-HDB3200

2Megapixel Full-HD Vandal-proof HD-SDI Dome Camera



- 1/3" 2Mp Exmor CMOS
- 25/30fps@1080p,50/60fps@720p
- Lens: 3.3~12mm/F1.4
- IR LEDs: 20m
- D&N(ICR), Auto Iris
- IK10 & IP66, AC24V/DC12V
- Material: Metal

HDC-HDBW3200

2Megapixel Full-HD Vandal-proof HD-SDI IR Dome Camera



- 1/3" 2Mp Exmor CMOS
- 25/30fps@1080p,50/60fps@720p
- Lens: 3.3~12mm/F1.4
- IR LEDs: 20m
- D&N(ICR), Auto Iris
- IK10 & IP66, AC24V/DC12V
- Material: Metal

PTZ Camera

SD6582A/82C-HS

2Mp Full-HD HD-SDI PTZ Dome Camera

- 1/3" 2Mp Exmor CMOS
- 25/30fps@1080p, 25/30/50/60fps@720p
- 4.7~94mm 20x optical zoom(82A), 4.3~129mm 30x optical zoom(82C)
- Max 400°/s pan speed
- DWDR, Defog(82C), D&N(ICR), DNR(2D&3D)
- 7/2ch alarm in/out
- IP67, IK 10 optional, -40 ~60 C

* Optional Model:

SD6582-HS: FCB-EH6300, 20x, WDR



SD6A82A/82C-HS

2Mp Full-HD HD-SDI IR PTZ Dome Camera

- 1/3" 2Mp Exmor CMOS
- 25/30fps@1080p, 25/30/50/60fps@720p
- 4.7~94mm 20x optical zoom(82A), 4.3~129mm 30x optical zoom(82C)
- Max 240°/s pan speed
- DWDR, Defog(82C), D&N(ICR), DNR(2D&3D)
- 7/2ch alarm in/out
- IP 66, -40~60°C
- IR LEDs up to 150m

* Optional Model:

SD6A82-HS: FCB-EH6300, 20x, WDR



Network PTZ Dome Camera

3 Megapixel

SD6583A-HN

3Mp WDR Full-HD Network PTZ Dome Camera

- 1/3" 3Mp CMOS
- Max 15fps@3Mp, 25/30fps@1080P
- 4.7~94mm 20x optical zoom
- H.264/MJPEG & Dual-stream encoding
- Max 400 °/s pan speed
- 100db WDR(1080P mode), D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 67, IK 10 optional, -40~60°C, Micro SD card



SD6983A-HN

3Mp WDR Full-HD Network IR PTZ Dome Camera

- 1/3" 3Mp CMOS
- Max 15fps@3Mp, 25/30fps@1080P
- 4.7~94mm 20x optical zoom
- H.264/MJPEG & Dual-stream encoding
- Max 240 °/s pan speed
- 100db WDR(1080P mode), D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 66, -40~60°C, Micro SD card
- IR LEDs up to 100m



2 Megapixel

SD6582A/82C-HN

2Mp Full-HD Network PTZ Dome Camera

- 1/3" 2Mp Exmor CMOS
- Max 25/30fps@1080P
- 4.7~94mm 20x optical zoom(82A), 4.3~129mm 30x optical zoom(82C)
- H.264/MJPEG & Dual-stream encoding
- Max 400 °/s pan speed
- DWDR, Defog(82C), D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 67, IK 10 optional, -40~60°C, Micro SD card

* *Optional Model:*

SD6582-HN: FCB-EH6300, 20x, WDR



SD6982A/82C-HN

2Mp Full-HD Network IR PTZ Dome Camera

- 1/3" 2Mp Exmor CMOS
- Max 25/30fps@1080P
- 4.7~94mm 20x optical zoom(82A), 4.3~129mm 30x optical zoom(82C)
- H.264/MJPEG & Dual-stream encoding
- Max 240 °/s pan speed
- DWDR, Defog(82C), D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 66, -40~60°C, Micro SD card
- IR LEDs up to 100m

* *Optional Model:*

SD6982-HN: FCB-EH6300, 20x, WDR



SD6A220/230-HN

2Mp Full-HD Network IR PTZ Dome Camera

- 1/3" 2Mp Exmor CMOS
- Max 25/30fps@1080P, 50/60fps@720P
- 4.7~94mm 20x optical zoom(220), 4.3~129mm 30x optical zoom(230)
- H.264/MJPEG & Dual-stream encoding
- Max 240 °/s pan speed
- DWDR, Defog(230), D&N(ICR), Ultra DNR
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 66, -40~70°C, Micro SD card
- IR LEDs up to 150m

* *Optional Model:*

SD6AS220-HN: FCB-EH6300, 20x, WDR



SD3282D-GN

2Mp Full-HD Network Mini PTZ Dome Camera

- 1/3" 2Mp Exmor CMOS
- Max 25/30fps@1080P
- 3~9mm 3x optical zoom
- H.264/MJPEG & Dual-stream encoding
- Max 120°/s Pan/Tilt speed, 0°~350° pan rotation
- DWDR, D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 2/1ch alarm in/out
- Micro SD card, PoE
- IP 66, IK 10 optional, -10~55°C



1.3 Megapixel

SD6580/80C-HN

1.3Mp HD Network PTZ Dome Camera

- 1/3" 1.3Mp CCD(80), 15fps@1.3M, 25/30fps@720p
- 1/3" 1.3Mp CMOS(80C), 25/30fps@1.3M/720p
- 4.7~84.6mm 18x optical zoom
- H.264/MJPEG & Dual-stream encoding
- Max 400 °/s pan speed
- 120db WDR(80C), D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 67, IK 10 optional, -40~60°C, Micro SD card

* *Optional Model:*

SD6581-HN: DI-SC110, 18x, CCD, WDR

SD6581B-HN: FCB-EH3410, 28x, CMOS, WDR

SD6581C-HN: DI-SC120R, 30x, CCD, WDR, Defog



SD6980/80C-HN

1.3Mp HD Network IR PTZ Dome Camera

- 1/3" 1.3Mp CCD(80), 15fps@1.3M, 25/30fps@720p
- 1/3" 1.3Mp CMOS(80C), 25/30fps@1.3M/720p
- 4.7~84.6mm 18x optical zoom
- H.264/MJPEG & Dual-stream encoding
- Max 240 °/s pan speed
- 120db WDR(80C), D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 66, -40~60°C, Micro SD card
- IR LEDs up to 100m

* *Optional Model:*

SD6981-HN: DI-SC110, 18x, CCD, WDR

SD6981B-HN: FCB-EH3410, 28x, CMOS, WDR

SD6981C-HN: DI-SC120R, 30x, CCD, WDR, Defog



SD6A120/130-HN

1.3Mp HD Network IR PTZ Dome Camera

- 1/3" 1.3Mp Exmor CMOS
- Max 25/30fps@1.3M, 50/60fps@720P
- 4.5~90mm 20x optical zoom(120), 4.3~129mm 30x optical zoom(130)
- H.264/MJPEG & Dual-stream encoding
- Max 240 °/s pan speed
- 120db WDR(130), Defog(130), D&N(ICR), Ultra DNR
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 66, -40~70°C, Micro SD card
- IR LEDs up to 150m

* Optional Model:

SD6A118-HN: CA-HZ1118, 18x, DWDR



SD63120S-HN

1.3Mp HD Cost-effective Network PTZ Dome Camera

- 1/3" 1.3Mp Exmor CMOS
- Max 25/30fps@1.3M/720P
- 4.5~90mm 20x optical zoom
- H.264/MJPEG & Dual-stream encoding
- Max 300 °/s pan speed
- DWDR, D&N(ICR), Ultra DNR
- 1/1ch audio in/out, 2/1ch alarm in/out
- IP 66, IK 10 optional, -40~60°C, Micro SD card



D1 Series

SD6C120S-HN

1.3Mp HD Cost-effective Network IR PTZ Dome Camera

- 1/3" 1.3Mp Exmor CMOS
- Max 25/30fps@1.3M/720P
- 4.5~90mm 20x optical zoom
- H.264/MJPEG & Dual-stream encoding
- Max 240 °/s pan speed
- DWDR, D&N(ICR), Ultra DNR
- 1/1ch audio in/out, 2/1ch alarm in/out
- IP 66, -40~60°C, Micro SD card
- IR LEDs up to 100m



SD6323C/23E/36E/70-HN

D1 Network PTZ Dome Camera

- 1/4" CMOS, 540TVL, 23x optical zoom(23C)
- 1/4" 960H CCD, 650TVL, 23x/36x optical zoom(23E/36E)
- 1/3" 960H CCD, 700TVL, 23x optical zoom(70)
- Max 25/30fps@D1(4CIF)/VGA
- 3.9~89.7mm 23x optical zoom(23C/23E/70), 3.4~122.4mm 36x optical zoom(36E)
- H.264/MJPEG & Dual-stream encoding
- DWDR(23E/36E/70), D&N(ICR), DNR(2D&3D)
- Max 300°/s pan speed
- 1/1ch audio in/out, 2/1ch alarm in/out
- IP 66, IK 10 optional, -40~60°C, Micro SD card

* Optional Model:

SD6363E-HN: FCB-EX490E, 18x, WDR
SD6365E-HN: FCB-EX995E, 28x, WDR
SD6366E-HN: FCB-EX1020, 36x, WDR



Auto-Tracking

SD6423C/23E/36E/70-HN

D1 Network IR PTZ Dome Camera

- 1/4" CMOS, 540TVL, 23x optical zoom(23C)
- 1/4" 960H CCD, 650TVL, 23x/36x optical zoom(23E/36E)
- 1/3" 960H CCD, 700TVL, 23x optical zoom(70)
- Max 25/30fps@D1(4CIF)/VGA
- 3.9~89.7mm 23x optical zoom(23C/23E/70), 3.4~122.4mm 36x optical zoom(36E)
- H.264/MJPEG & Dual-stream encoding
- DWDR(23E/36E/70), D&N(ICR), DNR(2D&3D)
- Max 240°/s pan speed
- 1/1ch audio in/out, 2/1ch alarm in/out
- IP 66, -40~60°C, Micro SD card
- IR LEDs up to 100m

* Optional Model:

SD6463E-HN: FCB-EX490E, 18x, WDR
SD6465E-HN: FCB-EX995E, 28x, WDR
SD6466E-HN: FCB-EX1020, 36x, WDR



SD6582A-HNI

2Mp Full-HD Network Auto-Tracking PTZ Dome Camera

- 1/3" 2Mp Exmor CMOS
- Max 25/30fps@1080P
- 4.7~94mm 20x optical zoom
- H.264/MJPEG & Dual-stream encoding
- Max 400 °/s pan speed
- Auto-tracking, IVS(Intelligent Video Surveillance)
- DWDR, D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 67, IK 10 optional, -40~60°C, Micro SD card

* Optional Model:

SD6582-HNI: FCB-EX6300, 20x, WDR



Positioning System

SD6A220/230-HNI

2Mp Full-HD Network Auto-Tracking IR PTZ Dome Camera

- 1/3" 2Mp Exmor CMOS
- Max 25/30fps@1080P, 50/60fps@720P
- 4.7~94mm 20x optical zoom(220), 4.3~129mm 30x optical zoom(230)
- H.264/MJPEG & Dual-stream encoding
- Max 240 °/s pan speed
- Auto-tracking, IVS(Intelligent Video Surveillance)
- DWDR, Defog(230),D&N(ICR), DNR(2D&3D)
- 1/1ch audio in/out, 7/2ch alarm in/out
- IP 66, -40~60°C, Micro SD card
- IR LEDs up to 150m

* Optional Model:

SD6AS220-HNI: FCB-EH6300, 20x, WDR



PTZ1182A-N

2MP Full-HD Network High-Speed Positioning System

- 1/3" 2Mp Exmor CMOS
- Max 25/30fps@1080P
- 4.7~94mm 20x optical zoom
- H.264/MJPEG & Dual-stream encoding
- DWDR, D&N(ICR), DNR(2D&3D)
- Pan Range: 360° Endless, Speed: 0.1~100°/sec
- Tilt Range: -90~40°, Speed: 0.1~40°/sec
- IP 66, -40~60°C
- 100m/200m IR LEDs optional



Network PTZ Dome Camera

Positioning System

PTZ1180C-N

1.3Mp HD Network High-Speed Positioning System

- 1/3" 1.3Mp CMOS
- Max 25/30fps@1.3M/720P
- 4.7~84.6mm 18x optical zoom
- H.264/MJPEG & Dual-stream encoding
- 100db WDR, D&N(ICR), DNR(2D&3D)
- Pan Range: 360° Endless, Speed: 0.1~100°/sec
- Tilt Range: -90~40°, Speed: 0.1~40°/sec
- IP 66, -40~60°C
- 100m/200m IR LEDs optional



Analog PTZ Camera

High Speed Dome

SD6523E/36E/70-H

23x/36x Quick-installation PTZ Dome Camera

- 1/4" 960H CCD, 650TVL, 23x/36x optical zoom(23E/36E)
- 1/3" 960H CCD, 700TVL, 23x optical zoom(70)
- DWDR, D&N(ICR), DNR (2D&3D)
- Max 400°/s pan speed
- 7/2ch alarm in/out
- IP 67, IK 10 optional, -40~60°C
- * *Optional Model:*
SD6563E-H: FCB-EX490E, 600TVL, 18x, WDR
SD6565E-H: FCB-EX995E, 600TVL, 28x, WDR
SD6566E-H: FCB-EX1020, 600TVL, 36x, WDR



Analog PTZ Camera

SD40/42/42C23C-H

23x Cost-effective Mini PTZ Dome Camera

- 1/4" CMOS, 540TVL
- 3.9~89.7mm 23x optical zoom
- Max 300°/s pan speed
- D&N(ICR), 2DNR
- 2/1ch alarm in/out
- IP 66, IK 10 optional, -40~60°C(40), -10~55°C(42/42C)



SD40/42/42C23-H

23x Mini PTZ Dome Camera

- 1/4" 960H CCD, 650TVL
- 3.9~89.7mm 23x optical zoom
- Max 300°/s pan speed
- DWDR, D&N(ICR), DNR(2D&3D)
- 2/1ch alarm in/out
- IP 66, IK 10 optional, -40~60°C(40), -10~55°C(42/42C)



SD6323C/23E/36E/70-H

23x/36x Cost-effective PTZ Dome Camera

- 1/4" CMOS, 540TVL, 23x optical zoom(23C)
- 1/4" 960H CCD, 650TVL, 23x/36x optical zoom(23E/36E)
- 1/3" 960H CCD, 700TVL, 23x optical zoom(70)
- DWDR(23E/36E/70), D&N(ICR), DNR (2D&3D)
- Max 300°/s pan speed
- IP 66, IK 10 optional, -40~60°C
- * *Optional Model:*
SD6363E-H: FCB-EX490E, 600TVL, 18x, WDR
SD6365E-H: FCB-EX995E, 600TVL, 28x, WDR
SD6366E-H: FCB-EX1020, 600TVL, 36x, WDR



SD6423C/23/30/36/70-H

23x/30x/36x Cost-effective IR PTZ Dome Camera

- 1/4" CMOS, 540TVL, 23x optical zoom(23C)
- 1/4" CCD, 600TVL, 23x/30x/36x optical zoom(23/30/36)
- 1/3" CCD, 700TVL, 23x optical zoom(70)
- DWDR, D&N(ICR), DNR (2D&3D)
- Max 240°/s pan speed
- IP 66, -40~60°C
- IR LEDs up to 80m
- * *Optional Model:*
SD6463E-H: FCB-EX490E, 600TVL, 18x, WDR
SD6465E-H: FCB-EX995E, 600TVL, 28x, WDR
SD6466E-H: FCB-EX1020, 600TVL, 36x, WDR



SD6923E/36E/70-H

23x/36x IR PTZ Dome Camera

- 1/4" 960H CCD, 650TVL, 23x/36x optical zoom(23E/36E)
- 1/3" 960H CCD, 700TVL, 23x optical zoom(70)
- DWDR, D&N(ICR), DNR (2D&3D)
- Max 240°/s pan speed
- 7/2ch alarm in/out
- IP 66, -40~60°C
- IR LEDs up to 100m
- * *Optional Model:*
SD6963E-H: FCB-EX490E, 600TVL, 18x, WDR
SD6965E-H: FCB-EX995E, 600TVL, 28x, WDR
SD6966E-H: FCB-EX1020, 600TVL, 36x, WDR



SD6923E/36E/70-G

23x/36x Cost-effective IR PTZ Dome Camera

- 1/4" 960H CCD, 650TVL, 23x/36x optical zoom(23E/36E)
- 1/3" 960H CCD, 700TVL, 23x optical zoom(70)
- DWDR, D&N(ICR), DNR (2D&3D)
- Max 240°/s pan speed
- IP 66, -40~60°C
- IR LEDs up to 80m
- * *Optional Model:*
SD6963E-G: FCB-EX490E, 600TVL, 18x, WDR
SD6965E-G: FCB-EX995E, 600TVL, 28x, WDR
SD6966E-G: FCB-EX1020, 600TVL, 36x, WDR



SD6A23E/36E/70-H

23x/36x IR PTZ Dome Camera

- 1/4" 960H CCD, 650TVL, 23x/36x optical zoom(23E/36E)
- 1/3" 960H CCD, 700TVL, 23x optical zoom(70)
- DWDR, D&N(ICR), DNR (2D&3D)
- Max 240°/s pan speed
- 7/2ch alarm in/out
- IP 66, -40~60°C
- IR LEDs up to 150m

* Optional Model:

SD6A63E-H: FCB-EX490E, 600TVL, 18x, WDR
SD6A65E-H: FCB-EX995E, 600TVL, 28x, WDR
SD6A66E-H: FCB-EX1020, 600TVL, 36x, WDR



SD6C23C/23E/36E/70-H

23x/36x Cost-effective IR PTZ Dome Camera

- 1/4" CMOS, 540TVL, 23x optical zoom(23C)
- 1/4" 960H CCD, 650TVL, 23x/36x optical zoom(23E/36E)
- 1/3" 960H CCD, 700TVL, 23x optical zoom(70)
- DWDR(23E/36E/70), D&N(ICR), DNR (2D&3D)
- Max 240°/s pan speed
- IP 66, -40~60°C
- IR LEDs up to 100m

* Optional Model:

SD6C63E-H: FCB-EX490E, 600TVL, 18x, WDR
SD6C65E-H: FCB-EX995E, 600TVL, 28x, WDR
SD6C66E-H: FCB-EX1020, 600TVL, 36x, WDR



Analog Camera

Mega HDIS Series

CA-FW191G

HDIS Day/Night Water-proof IR Bullet Camera



- 800TVL, 1/3" 1.3Mega HDIS, ICR, 3D-DNR
- 6mm fixed lens (2.8 mm, 3.6mm, 8mm optional)
- IR LEDs: 20m, Smart IR
- IP66, DC12V
- Default: with Bracket
- Material: Metal

FW191D

HDIS Day/Night Waterproof IR Bullet Camera



- 800TVL, 1/3" 1.3Mega HDIS, ICR, 3D-DNR
- 6mm fixed lens (2.8 mm, 3.6mm, 8mm optional)
- Max. IR LEDs length 30m, Smart IR
- IP66, DC12V
- Material: Metal(front)+Plastic(body)

CA-FW191J

HDIS Day/Night Waterproof IR Bullet Camera



- 800TVL, 1/3" 1.3Mega HDIS, ICR, 3D-DNR
- 8mm fixed lens (3.6mm, 6mm, 12mm, 16mm optional)
- Max. IR LEDs length 50m, Smart IR
- IP66, DC12V
- Material: Metal(front)+Plastic(body)

CA-D190C

HDIS Mini Dome Camera



- 800TVL, 1/3" 1.3Mega HDIS, 3D-DNR
- Lens: 3.6mm(2.8mm, 6mm, 8mm optional)
- Advanced tri-axis structure adopted & support 355° pan
- DC12V
- Material: Plastic

CA-DW191H

HDIS Day/Night IR Mini Dome Camera



- 800TVL, 1/3" 1.3Mega HDIS, ICR, 3D-DNR
- 3.6mm fixed lens (2.8mm, 6mm, 8mm optional)
- Max. IR LEDs length 20m, Smart IR
- DC12V
- Material: Plastic

CA-DW191E

HDIS Water-proof IR Mini Dome Camera



- 800TVL, 1/3" 1.3Mega HDIS, ICR, 3D-DNR
- 3.6mm fixed lens (2.8mm, 6mm, 8mm optional)
- Max. IR LEDs length 20m, Smart IR
- IP66, DC12V
- Material: Metal(Inner core)+Plastic(Outside)

HDIS Series

CA-FW181G/171G/161G

HDIS Day/Night Water-proof IR Bullet Camera



- FW181G: 720TVL, 1/3" HDIS, ICR
- FW171G: 600TVL, 1/3" HDIS, ICR
- FW161G: 540TVL, 1/3.7" HDIS, ICR
- 6mm fixed lens (2.8 mm, 3.6mm, 8mm optional)
- IR LEDs: 20m
- IP66, DC12V
- Default: with Bracket
- Material: Metal

FW161K

HDIS Day/Night Water-proof IR Bullet Camera



- 540TVL, 1/3.7" HDIS, ICR
- Lens: 6mm(2.8mm, 3.6mm, 8mm optional)
- IR LEDs: 30m, Smart IR
- IP66, DC12V
- Material: Metal(front)+Plastic(body)

FW181D/171D

HDIS Day/Night Waterproof IR Bullet Camera



- FW181D: 720TVL, 1/3" HDIS, ICR
- FW171D: 600TVL, 1/3" HDIS, ICR
- 6mm fixed lens (2.8 mm, 3.6mm, 8mm optional)
- Max. IR LEDs length 30m, Smart IR
- IP66, DC12V
- Material: Metal(front)+Plastic(body)

Analog Camera

HDIS Series

CA-FW181J

HDIS Day/Night Waterproof IR-Bullet Camera



- 720TVL, 1/3" HDIS, ICR
- 8mm fixed lens (3.6mm, 6mm, 12mm, 16mm optional)
- Max. IR LEDs length 50m, Smart IR
- IP66, DC12V
- Material: Metal(front)+Plastic(body)

CA-FW171

HDIS Day/Night Water-proof IR-Bullet Camera



- 600TVL, 1/3" HDIS, ICR
- 2.8~12mm varifocal lens
- IR LEDs: 30m, Smart IR
- IP66, DC12V
- Default: with bracket
- Material: Metal

CA-D180C/170C

HDIS Mini Dome Camera



- D180C: 720TVL, 1/3" HDIS
- D170C: 600TVL, 1/3" HDIS
- Lens: 3.6mm(2.8mm, 6mm, 8mm optional)
- Advanced tri-axis structure adopted & support 355° pan
- DC12V
- Material: Plastic

CA-DW181H/161H

HDIS Day/Night IR Mini Dome Camera



- DW181H: 720TVL, 1/3" HDIS, ICR
- DW161H: 540TVL, 1/3.7" HDIS, ICR
- 3.6mm fixed lens (2.8mm, 6mm, 8mm optional)
- Max. IR LEDs length 20m, Smart IR
- DC12V
- Material: Plastic

CA-DW181E/171E

HDIS Day/Night Water-proof IR Mini Dome Camera



- DW181E: 720TVL, 1/3" HDIS, ICR
- DW171E: 600TVL, 1/3" HDIS, ICR
- 3.6mm fixed lens (2.8mm, 6mm, 8mm optional)
- Max. IR LEDs length 20m, Smart IR
- IP66, DC12V
- Material: Metal(inner core)+Plastic(Outside)

CA-DW171F

HDIS Day/Night IR Dome Camera



- 600TVL, 1/3" HDIS, ICR
- Lens: 3.6mm(2.8mm, 6mm, 8mm optional)
- IR LEDs: 20m
- DC12V
- Material: Plastic

CA-DW171C

HDIS Day/Night Water-proof IR Dome Camera



- 600TVL, 1/3" HDIS, ICR
- Lens: 3.6mm(2.8mm, 6mm, 8mm, 12mm optional)
- IR LEDs: 50m
- IP66, DC12V
- Material: Metal

CA-DW171B

HDIS Day/Night IR Dome Camera



- 600TVL, 1/3" HDIS, ICR
- 2.8~12mm varifocal lens
- IR LEDs: 20m, Smart IR
- IP66, DC12V(AC24V optional)
- Material: Plastic

Effio Series

CA-F481E/581E/681E/781E

Day/Night Box Camera



- F481E: 700TVL, 1/3" EXview HAD CCD II, ICR
- F581E: 700TVL, 1/3" Super HAD CCD II, ICR, WDR
- F681E: 700TVL, 1/3" EXview HAD CCD II, ICR, HLS
- F781E: 700TVL, 1/3" EXview HAD CCD II, ICR, Low Light
- Auto iris, OSD, adjustable back focus
- AC24V/DC12V
- Material: Metal

CA-F480F

Cost-effective Box Camera



- 700TVL, 1/3" EXview HAD CCD II
- Auto iris, OSD, adjustable back focus
- DC12V
- Material: Plastic

CA-FW480D/480H

Water-proof IR-Bullet Camera



- 700TVL, 1/3" EXview HAD CCD II
- Lens: 6mm(3.6mm, 3.6mm, 8mm, 12mm optional)
- Max IR LEDs: 50m, Smart IR
- IP66, DC12V
- Material: Metal(front)+Plastic(body)
- FW480H: Default with bracket

CA-FW480C

Water-proof IR-Bullet Camera



- 700TVL, 1/3" EXview HAD CCD II
- Lens: 6mm(2.8mm, 3.6mm, 8mm, 12mm, 16mm optional)
- IR LEDs: 50m
- IP66, DC12V
- Material: Metal

CA-FW480E

Waterproof IR-Bullet Camera



- 700TVL, 1/3" EXview HAD CCD II
- Motorized Lens: 4~9mm(8~20mm optional)
- IR LEDs: 50m(100m optional), Smart IR
- IP66, DC12V, OSD
- Default: with Bracket
- Material: Metal(front)+Plastic(body)

CA-FW480

Water-proof IR-Bullet Camera



- 700TVL, 1/3" SONY EXview HAD CCD II
- Lens: 4~9mm(2.8~12mm optional)
- 2BNC out, IR LEDs: 30m, Smart IR
- IP66, DC12V(AC24V optional)
- Default: with Bracket
- Material: Metal

CA-DB480C

Vandal-proof Mini Dome Camera



- 700TVL, 1/3" EXview HAD CCD II
- Lens: 3.6mm(2.8mm, 6mm, 8mm, 12mm optional)
- OSD, IK10, IP66, DC12V
- Material: Metal

CA-D480C

Enhanced Mini Dome Camera



- 700TVL, 1/3" EXview HAD CCD II
- Lens: 3.6mm(2.8mm, 6mm, 8mm, 12mm optional)
- OSD, DC12V
- Material: Plastic

CA-D480B/581B

Dome Camera



- D581B: 700TVL, 1/3" Super HAD CCD II, WDR, ICR
- D480B: 700TVL, 1/3" EXview HAD CCD II
- Lens: 4.0~9.0mm(2.8~12mm optional)
- Auto iris, OSD
- DC12V(AC24V optional)
- Material: Plastic

CA-DW480B/481B

IR Dome Camera



- DW480B: 700TVL, 1/3" SONY EXview HAD CCD II
- DW481B: 700TVL, 1/3" SONY EXview HAD CCD II, ICR
- 4.0~9.0mm(2.8~12mm optional)
- IR LEDs: 20m, Smart IR
- Auto iris, OSD
- DC12V(AC24V optional)
- Material: Plastic

CA-DB480B/581B

Vandal-proof Dome Camera



- DB480B: 700TVL, 1/3" EXview HAD II CCD
- DB581B: 700TVL, 1/3" Super HAD CCD II, WDR, ICR
- Lens: 4~9mm(2.8~12mm optional)
- Auto iris, OSD
- IK10, IP66, DC12V(AC24V optional)
- Material: Metal

CA-DBW480B/481B/581B

Vandal-proof IR Dome Camera



- DBW480B: 700TVL, 1/3" SONY EXview HAD CCD II
- DBW481B: 700TVL, 1/3" SONY EXview HAD CCD II, ICR
- DBW581B: 700TVL, 1/3" Super HAD CCD II, ICR, WDR
- 4.0~9.0mm(2.8~12mm optional)
- IR LEDs: 20m, Smart IR
- Auto iris, OSD,
- IK10, IP66, DC12V(AC24V optional)
- Material: Metal

CA-DW480C

Water-proof IR Dome Camera



- 700TVL, 1/3" EXview HAD CCD II
- Lens: 3.6mm(2.8mm, 6mm, 8mm, 12mm, 16mm optional)
- Max IR LEDs Length: 50m
- IP66, DC12V
- Material: Metal

Pinhole Series

CA-DW480E

Water-proof IR Mini Dome Camera



- 700TVL, 1/3" EXview HAD CCD II
- Lens: 6mm(2.8mm, 3.6mm, 8mm optional)
- IR LEDs: 20m, Smart IR
- IP66, DC12V
- Material: Metal(inner core)+Plastic(outside)

CA-UM480B/580B

Pinhole Camera



- CA-UM480B: 700TVL, 1/3" EXview HAD CCD II
- CA-UM580B: 700TVL, 1/3" Super HAD CCD II, WDR
- Lens: 3.6mm(2.8mm optional)
- OSD, DC12
- Material: Metal

Mobile Series

CA-M161E

HDIS Day/Night Mobile Dome Camera



- 540TVL, 1/3.7" HDIS, ICR
- Lens: 3.6mm(2.8mm optional)
- Aviation connector, shock-proof
- Default: with Pickup
- DC12V
- Material: Metal

Analog Camera

CA-MW161E

HDIS Day/Night IR Mobile Dome Camera



- 540TVL, 1/3.7" HDIS, ICR
- Lens: 3.6mm(2.8mm optional)
- IR LEDs:10m
- Aviation connector, shock-proof
- Default: with Pickup
- DC12V
- Material: Metal

CA-D480D

Mobile Dome Camera



- 700TVL, 1/3" EXview HAD CCD II
- Lens: 3.6mm(2.8mm optional), DC12
- Aviation connector, shock-proof
- Default: with Pickup
- DC12V
- Material: Metal

CA-DW480D

IR Mobile Dome Camera



- 700TVL, 1/3" EXview HAD CCD II
- Lens: 3.6mm(2.8mm optional)
- IR LEDs: 10m
- Aviation connector, shock-proof
- Default: with Pickup
- DC12V
- Material: Metal

Zoom Series

CA-F7823B

Day/Night Zoom Camera



- 700TVL, 1/3" SONY EXview HAD CCD II, ICR, 3D-DNR
- Auto iris, Auto focus, OSD
- 23x optical zoom
- DC 9~12V
- Material: Plastic

CA-F7623B

Day/Night Zoom Camera



- 600TVL, 1/4" Super HAD CCD II, ICR, 3D-DNR
- Auto iris, Auto focus, OSD
- 23x optical zoom
- DC 9~12V
- Material: Plastic

CA-F7636B

Day/Night Zoom Camera




- 600TVL, 1/4" Super HAD CCD II, ICR, 3D-DNR
- Auto iris, Auto focus, OSD
- 36x optical zoom
- DC 9~12V
- Material: Plastic

Compression Card

HD-SDI

VEC8104HD

4CH HD-SDI Full-HD Cost-effective PCI-E Compression Card




- 4ch video & audio
- 1080p/1080i/720p HD-SDI video input
- H.264 & Dual-stream encoding
- 4 channel@1080p realtime recording
- 1ch HDMI 1080p Matrix output
- Windows/Linux, PCI-E

960H

VEC8116HF-E

16CH 960H PCI-E Compression Card




- 16ch video & audio
- H.264 & Dual-stream encoding
- All channel@960H realtime recording
- 1ch HDMI 1080p Matrix output
- Windows/Linux, PCI-E

D1

VEC8008/8016HB

8/16CH D1 Compression Card




- 8/16ch video & audio
- H.264 & Dual-stream encoding
- All channel@D1(4CIF) realtime recording
- 1/2ch TV Matrix output
- Windows/Linux, PCI

CIF

VEC8008/8016HB-E

8/16CH D1 PCI-E Compression Card



- 8/16ch video & audio
- H.264 & Dual-stream encoding
- All channel@D1(4CIF) realtime recording
- 1/2ch Matrix output
- Windows/Linux, PCI-E

VEC0804/1604LC

8/16CH CIF Compression



- 8/16ch video & audio
- H.264 & Dual-stream encoding
- All channel@CIF realtime recording
- Windows/Linux, PCI

Network Video Server

Encoder

NVS0104/0204/0404HE(-E/-C/-W)

1/2/4CH H.264 Network Video Server



- 1/2/4ch video inputs
- 1/2/4ch audio in & 1ch audio out, 1ch Mic in
- All channel@D1 realtime recording
- 4/2ch alarm in/out, RS485, RJ45(100M)
- Hot swappable SD card
- 3G (-E/-C only); Wi-Fi(-W only)

NVS0104/0204/0404HE-AS(-E/-C/-W)

1/2/4CH H.264 Network Video Server



- 1/2/4ch video inputs
- 1/2/2ch audio in & 1ch audio out
- All channel@D1 realtime recording
- 4/1ch alarm in/out, RS485, RJ45(100M)
- 3G (-E/-C only); Wi-Fi(-W only)
- 1SATA, 1USB

NVS0404/0804/1604HF-A(-E/-C/-W)

4/8/16CH H.264 Real-time Network Video Server



- 4/8/16ch video
- 4/8/4ch audio in & 1ch audio out, 1ch Mic in
- All channel@D1 realtime recording
- 4/8/16ch alarm in & 3 relay out, RS485, RJ45(100M)
- 3G (-E/-C only); Wi-Fi(-W only)
- 2SATA, 2USB

Matrix

Decoder

NVS0104DH

1CH Full HD Network Video Decoder



- Support IPC, DVR, NVS, CMS
- H.264/MPEG-4 dual codec
- 16ch@D1/8ch@720P/4ch@1080P decoding
- 1 HDMI & 1VGA & 1 TV display
- 16/8ch alarm in/out
- RJ45(1000M)

NVS0404DH

4CH Full HD Network Video Decoder



- Support IPC, DVR, NVS, CMS
- H.264/MPEG-4 dual codec
- 28ch@D1, 14ch@720P, 7ch@1080P decoding,
- 4 HDMI & 4 VGA & 4 TV display
- 16/8ch alarm in/out
- RJ45(1000M)

DH-M60

12U Matrix Platform



- 80ch@1080p IP camera inputs, storage and transmission
- 1280ch@D1 or 160ch HD decoding & 320ch@D1 or 80ch HD encoding
- Signal Input: Analog/Digital, HD/SD mix input
- Signal Output: Matrix switch output, non-compression Digital output
- 10 function card (hotswappable) slots
- Support video-wall splicing, intelligent analysis and etc.

Storage

Network Storage

ESS3116X

16HDD Network Storage



- 192ch@D1,96ch@720P,48ch@1080P
- 16 HDDs supported(each one up to 3TB)
- Raid0,Raid1,Raid5,Raid6,JBOD,Single
- iSCSI, SAMBA, NFS, FTP
- HDD expansion: four expansion device
- 2 expansion Mini SAS
- 4 RJ-45 10/100/1000Mbps

ESS3116S-J

16HDD Storage Extension Cabinet



- 16 SATA II (each one up to 3TB)
- Independent HDD support, Hot-swappable
- 2-SAS 2.0-port (6Gbps)
- Support SBB2.0 standard
- Case management adopt SES protocol

eSATA Storage

ESS1504A

4HDD eSATA Storage



- 4 SATA HDDs, support up to 16TB
- W/R capacity: Write >40MB/s, Read >70MB/s
- Support all NVR/DVRs with eSATA port
- Standard 1.5U case

Video-Wall

Display Unit

DHL460UT

46" Full-HD LCD Display Unit



- 46"(16:9) diagonal size
- Industrial DID LCD panel, LED backlight
- Full HD resolution
- 700cd/m²
- 8ms fast response time
- CVBS(BNC)/HDMI/DVI/VGA (D-Sub) input

Multiple Screen Standalone Controller

DSCON1000

Multiple Screen Standalone Controller



- OS-free,virus-free,high stability
- 9CH HD output, 4CH video input
- Easy video-wall play configuration,support roam, overlay, zoom
- Build-in decoder function, support dahua IPC/DVR to decode
- Support Smart PSS

DSCON2000

Multiple Screen Standalone Controller



- OS-free,virus-free,high stability
- 16CH HD output, 24CH video input
- Easy video-wall play configuration, support roam, overlay, zoom
- Support Smart PSS
- Hot-swap

Accessories

Keyboard

NKB/KBDB

Network Keyboard & Control Keyboard



- For DVR, NVS, PTZ Dome Camera
- RS232, RS485 & Network Connections
- Joystick Control & PTZ Functions

NKB-3000

HD Network Keyboard



- For DVR, NVS, PTZ Dome Camera control
- RS232, RS485 & Network Connections
- 4D-joystick Control & PTZ Functions
- Support 1080p realtime preview
- Support HDMI/VGA/TV(BNC) syn video output
- Support Video-Wall display, bidirectional talk
- Touch screen, external Wi-Fi

HD-SDI Repeater/Splitter

CON102SR/CON108SS

HD-SDI Repeater / Splitter



- 1/2 in/out HD-SDI Repeater(CON102SR)
- 1/8 in/out HD-SDI Splitter(CON108SS)
- Standard HD-SDI high definition digital interface (SMPT274/292)
- 100m~120m transmission distance extension
- Thunder & surge proof and effectively prevent the electromagnetic wave interference
- DC12V

Software

CMS

DSS

Digital Surveillance System



- Max 5000 channel connection
- C/S, B/S structure network surveillance system
- Support DVR, SVR, NVR, NVS, IPC, NVD and etc.
- Multi-level management system
- Used for large-scale & important applications

PSS

Pro Surveillance System



- Max 1000 channel connection
- Max 121(11x11)video live view
- Support DVR, SVR, NVR, NVS, IPC, NVD and etc.
- Support Multi-screen
- Used for central monitoring system



DMSS

Mobile Phone Surveillance Software



- For iOS: iPhone(iDMSS Plus) & iPad (iDMSS HD)
- For Android: Phone & Kindle Fire(gDMSS Plus), Tablet (gDMSS HD)
- For Windows Phone8(wDMSS Plus)
- For Windows Phone(DMSS)
- Main/Extra stream Preview & Playback, DDNS sync(Cloud Device)
- Multi-language, Push Notification, Remote Configuration, HDD report, E-map
- Local Recording, Alarm out, Favorites Group, Color Setting, QR Code Scanning



DAHUA TECHNOLOGY CO., LTD.

No.1187 Bin'an Road, Binjiang District, Hangzhou, China. 310053
 Tel: +86-571-87688883 Fax: +86-571-87688815
 Email: overseas@dahuatech.com
 www.dahuasecurity.com

